



TURBO TORQUE LIFE 2 ***Diesel Engine Oil***

DESCRIPTION

TURBO TORQUE LIFE 2 is high quality diesel engine oil formulated with paraffinic base mineral oils and an excellent additives package that protects the engine from oxidation, wear, rust and gives impressive thermal stability to the engine. DUTY LIFE 1 meets the requirements of API CD service category.

APPLICATION

TURBO TORQUE LIFE 2 oils are recommended for use in high speed, high load, and super charged diesel engines where manufacturers have recommended use in engines.

BENEFITS

- Excellent protection power from rust, wear and oxidation.
- Provides excellent thermal stability.
- Protects against deposit/sludge formations.
- Extends the engine's life period.

PERFORMANCE

API CD

TURBO TORQUE LIFE 2 available in 10W, 20, 30, 40 and 50 SAE Grade





PRODUCT DATA SHEET

Specifications

Test Parameter	Units	Test Limits					Test Method
		10W	20	30	40	50	
SAE Grade		10W	20	30	40	50	
Appearance	-	C&B	C&B	C&B	C&B	C&B	Visual
Density @ 15°C	Kg/m3	0.87	0.878	0.88	0.89	0.90	ASTM D-4052
Viscosity @ 40°C	cSt	25	28	70	148	216	ASTM D-445
Viscosity @ 100°C	cSt	4.1 min.	5.6 – 9.2	9.3 – 12.4	12.5 – 16.2	16.3 – 21.8	ASTM D-445
Viscosity Index, min.	-	104	100	98	95	95	ASTM D- 2270
Flash Point (COC), min.	°C	216	222	230	246	250	ASTM D-92
Pour Point, max.	°C	-21	-18	-9	-6	-6	ASTM D-97
Base Number, min	mg of KOH/gr	7	7	7	7	7	ASTM D-2896
CODE		410/1	410/2	410/3	410/4	410/5	

