



PL9

Automatic Transmission Fluid

DESCRIPTION:

PL 9 is formulated from high quality Synthetic base oils and a high quality additives package to enhance the multi-functional properties of automatic transmission systems and electrical steering and hydraulic systems. It meets the requirements of vehicles and other industrial equipment where DEXRON VI specifications are recommended. PL9 specially designed for high speed passenger cars where 8 and 9 speed is found

APPLICATION:

PL9 is recommended for use in automatic gear boxes, steering systems, and hydraulic systems where manufacturers recommend using DEX VI and Ford MERCON LV oil specifications especially for 8 and 9 speed passenger cars

BENEFITS

- Provides excellent thermal stability in systems.
- Excellent oxidation resistance.
- Excellent low temperature fluidity.
- Protects against rust and corrosion.
- Smooth gear shifting properties.
- Excellent viscosity stability.
- Outstanding gears wear protection.
- Excellent transmission cleanliness properties

PERFORMANCE

DEXRON VI

Ford MERCON LV

ZF 8HP 45 and ZF 9HP 45





PRODUCT DATA SHEET

Specifications

Test Parameter	Units	Test Limits	Test Method
Appearance	-	C&B	Visual
Color	-	brown	Visual
Density @ 15°C	g/cm ³	0.848	ASTM D-4052
Viscosity @ 40°C	cSt	28.7	ASTM D-445
Viscosity @ 100°C	cSt	6.4	ASTM D-445
Viscosity Index	-	185	ASTM D- 2270
Flash Point (COC), min.	°C	210	ASTM D-92
Pour Point	°C	-51	ASTM D-97
Foaming character	ml/ml	0/0	ASTM D-892

